



CE

| | | | |
|------------------|-----------------------|--------------------|---------------|
| Power | 40 W | Voltage | 230 V |
| Luminous flux* | 5100 lm (360°) | Colour temperature | 3000 K |
| Light colour | WW | Beam angle | 120 ° |
| Protection class | IP20 | | |



 User manual



 Declaration of Conformity



 Photometric file

Technical data:

| | |
|------------------------------|---------------------------|
| Product code | SLI035067WW_PW |
| Power | 40 W |
| Nominal current | 185 mA |
| Voltage | 230 V |
| Energy consumption | 40 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | I |
| Power supply included | + |
| Power factor | 0.9 |
| Useful luminous flux* | 5100 lm (360°) |
| Luminous flux** | 4500 lm (360°) |
| Light efficiency | 128 lm/W |
| Colour temperature | 3000 K |
| Light colour | WW |
| Beam angle | 120 ° |
| RA | >80 |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20/+40 ° |
| Lifespan | 50000 h |
| Housing material | Aluminum/Plastic |
| Protection class | IP20 |
| Colour | White |
| Dimension (axbxc) | 295x1195x32 mm |
| For use | Inside |
| Assembly method | surface mounted, recessed |
| Application | INT |
| Made in | PRC |



*Applies to the LED source used. **Luminaire luminous flux