




CE

Power	<b>100 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>15500 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>90 °</b>
IK	<b>09</b>	Protection class	<b>IP65</b>




See more on dedicated page 



 User manual




 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI044024NW_PW
Power	100 W
Nominal current	450 mA
Voltage	230 V
Energy consumption	100 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.95
Useful luminous flux*	15500 lm (360°)
Luminous flux**	15000 lm (360°)
Light efficiency	155 lm/W
Luminous intensity	7000 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	90 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	1-10V
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PC
IK	09
Protection class	IP65
Colour	Black
Dimension (axbxc)	250x120 mm
For use	Inside/Outside
Assembly method	Suspended
Application	INT/EXT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux