



Power	5 W	Voltage	230 V
Luminous flux*	480 lm (90°)	Colour temperature	2700-6500 K
Light colour	CCT/RGB	Beam angle	50 °
Protection class	IP20		



 Declaration of Conformity

MDR40EC05RGBW50W

Technical data:

Product code	WOJP06252
Power	5 W
Nominal current	45 mA
Voltage	230 V
Energy efficiency classe	E
Energy consumption	5 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Manufacturer of power supply	SMART
Power factor	0,5
Useful luminous flux*	480 lm (90°)
Luminous flux**	480 lm (360°)
Light efficiency	96 lm/W
Luminous intensity	480 cd
Colour temperature	2700-6500 K
Light colour	CCT/RGB
Beam angle	50 °
RA	80
Light source included	+
Uniformity of color SDCM max	3
Dimmable	SMART
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum
Protection class	IP20
Colour	White
Dimension (axbxc)	50x175x145 mm
For use	Inside
Assembly method	On 3-circuit system
Application	INT
Made in	PL
Other	RGBW ,



*Applies to the LED source used. **Luminaire luminous flux

*Luminaire with the ability to change the color of light (2700 - 6500K) or dimming by application Spectrum SMART.